PART II

Reasoning About Mechanical Devices

The overall goal of the FONM representation theory is to support the design and implementation of computational models of mechanical reasoning, particularly improvisation and invention. As a creative problem-solving task, invention can be viewed as an integration of four reasoning tasks: (1) problem recognition, (2) problem interpretation, (3) problem evaluation, and (4) experimentation. This part of the dissertation presents two computational models constructed while developing FONM. Each model makes use of specific aspects of the FONM representation of devices, and demonstrates recognition of knowledge and inference-making capability in its reasoning domain.

Knowing how it could change the lives of canines everywhere, the dog scientists struggled diligently to understand the Doorknob Principle.

Chapter 6
Mechanical Experimentation

This chapter presents a program which performs mechanical simulation. EDEXP (EDison EXPerimenter) is a computer program that takes the symbolic representation of a simple mechanical door, mutates the door by moving a hinge, simulates the capacity of the door to move, by moving the hinge to different locations, and identifies the relationship between hinge behavior and door rotation. To accomplish this task, EDEXP implements the FONM theory of MOTION and RESTRAIN behavioral primitives.

In this chapter, the reasoning processes associated with hypothesizing, executing, and interpreting the results of mechanical experiments are discussed with respect to their dependency on how knowledge of mechanical behavior is represented and manipulated. The EDEXP model is presented and applied to a door manipulation example.

6.1 Computational Architecture

The two models presented in this and the next chapter utilize the computational architecture from the EDISON project, but have been implemented using different versions of FONM and different computational approaches. As such, those components of the architecture which are specific to each program are presented with respect to the kind of I/O and behavior that the program produces.

6.1.1 EDEXP

EDEXP implements four components of the EDISON computational architecture (Fig. 6.1): (1) a planning demon interpreter, (2) rules for performing planning analysis, mutation, and recognition (3) a planning memory, and (4) a long term memory of abstract patterns associated with devices, device plans, and device behaviors.



Figure 6.1 The components of EDEXP. Thick solid lines represent inter-memory access. Thick dotted lines represent control access to memories and rules from demon interpreters. Thin dotted lines represent input/output data flow.

- **Semantic Memory (SM)**. Semantic memory represents schematic knowledge of objects, events, and their causal interactions. In EDEXP, SM is comprised of frame-based rules which describe object behavior according to the FONM behavioral process definitions. During planning and behavioral simulation, input conceptualizations are compared to their counterparts in semantic memory, which are used to instantiate incomplete frames.

- **Planning Demon Interpreter (PDI)**. The planning interpreter uses demons to process goals and plans by recursively matching their subgoals to planning memory and comparing the subgoals to the overall task. The interpreter functions in a two modes: (1) experimentation, and (2) hypothesis testing. During experimentation mode, the plans associated with the experiment and device are instantiated with the intent of generalizing a hypothesis which relates the goal and device. During hypothesis testing mode, the planner applies the hypothesis to the chosen plan and device templates to attempt to prove the hypothesis.

- **Planning Memory (PM)**. During planning, EDEXP uses instantiated conceptual frames initially placed onto a memory called *planning memory*. Planning memory serves as a memory retrieval source for reasoning since the items accessed from memory represent the episodic input. Planning memory is maintained until a plan is analyzed.